

**CHAPTER-7**  
**DAMP PROOF COURSE**

S.No.	SCH. P.W.D	ITEM NO NBO	Description of Work	P.W.D SPEC. NO.	UNIT	LABOUR RATE	OVER ALL RATE
1	2	3	4	5	6	7	8
1	360		2cm (3/4") thick damp proof course with cement and approved coarse sand 1:2 with and including water proofing materials as ordered by the Engineer in charge in the proportion as specified by the manufacturers including supply of all material, labour and T&P etc. required for proper completion of the work including proper curing and shuttering as necessary.		sqm		200.00
2	361		As in item (360) above but 2.5 cm (1") thick and of cement concrete consisting of one part cement 1½ parts approved coarse sand and 3 parts approved 13mm (1½) graded stone grit and including water proofing materials as ordered by the Engineer-in-charge in the proportion as specified by the manufacturers.		sqm		290.00
3	361(b)		40 mm thick damp proof course of cement concrete consisting of 1:1.5:3 one part cement 1.5 parts approved coarse sand and 3 parts approved 13mm graded stone grit and including water proofing materials as ordered by the Engineer-in-charge in the proportion as specified by the manufacturers including supply of all material, labour and tools and plants etc, required for proper completion of the work including proper curing and shuttering as necessary.		Sq.M		400.00
4		NS	Painting on D.P.C with two coats of airblown bitumen 85/50 or 85/25 @ 1.7 Kg/Sq. M. approx including cost of fuel if any.		Sq.M		70.00